

CIMCLEAN® PRODUCTO™ SP-220



DESCRIPTION

CIMCLEAN PRODUCTO SP-220 is a water-based, non-foaming liquid detergent.

APPLICATION

CIMCLEAN PRODUCTO SP-220 is intended primarily for use in the removal of coolants, machining fluids, honing oils, and greases from machined steel surfaces in high pressure applications.

FEATURES & BENEFITS

- Provides excellent corrosion protection on ferrous metals.
- Leaves no solid residues which can interfere with electronic gauging operations and does not leave water spots. Residue is a clear, mobile liquid.
- It is ashless, making it ideal for use in washers prior to heat-treat ovens.
- Rejects oil for enhanced washer cleanliness and extended sump life.
- Does not contain DEA, phosphates, silicates, EDTA, NTA, or nitrites
- Responds readily to conventional waste treatment procedures.

RECOMMENDED STARTING DILUTIONS:

CIMCLEAN PRODUCTO SP-220 is to be mixed with water for use. Always add concentrate to water. Add no other materials to the concentrate or mix unless approved by your CIMCOOL® District Manager.

Spray Washers: 3% to 5% (0.6 – 1.0 on the refractometer scale)

• Refractometer Factor: 5.0

4% Mix pH is typically 10.2

HANDLING and STORAGE:

If frozen, thaw completely at room temperature. Inside storage is recommended.

SAFETY DATA SHEET:

Available at www.cimcool.com

For additional information refer to its OSHA SDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL® Technical Services at 1-888-CIMCOOL.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.

CIMCOOL FLUID TECHNOLOGY 3000 DISNEY STREET CINCINNATI, OH 45209 1/2019 PC B40000

