

CIMCLEAN[®] PRODUCTO[™] SP-2238R



DESCRIPTION

CIMCLEAN PRODUCTO SP-2238R is a water-based, low-foaming, liquid detergent.

APPLICATION

CIMCLEAN PRODUCTO SP-2238R is intended primarily for use in the removal of coolants, machining fluids, and honing oils from ferrous and aluminum metal surfaces in high pressure applications.

FEATURES & BENEFITS

- Provides superior corrosion protection on ferrous and aluminum metals without leaving a visible or tacky film.
- Effectively removes, suspends, and prevents re-deposition of the fine particulate “smut” formed in honing operations.
- Rejects oil for enhanced washer cleanliness and sump life.
- Responds readily to conventional waste treatment procedures.

RECOMMENDED STARTING DILUTIONS:

CIMCLEAN PRODUCTO SP-2238R is to be mixed with water for use. Always add concentrate to water. Add no other materials to the concentrate or mix unless approved by your CIMCOOL[®] District Manager.

- Spray Washers: 3% to 5% (0.83 – 1.39 on the refractometer scale)
- Refractometer Factor: 3.6
- 4% Mix pH is typically 9.1

HANDLING and STORAGE:

If frozen, thaw completely at room temperature. Inside storage is recommended.

SAFETY DATA SHEET:

Available at www.cimcool.com

For additional information refer to its OSHA SDS on www.cimcool.com website, or contact your local CIMCOOL[®] Technical Service Specialist or you may contact CIMCOOL Technical Services at 1-888-CIMCOOL.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.