

CIMCLEAN[®] PRODUCTO[™] SP-262T



DESCRIPTION

CIMCLEAN PRODUCTO SP-262T is a water-based, low-foaming detergent.

APPLICATION

CIMCLEAN PRODUCTO SP-262T is intended primarily for use in the removal of coolants, machining fluids, and honing oils from machined steel surfaces in high pressure applications.

FEATURES & BENEFITS

- Provides excellent rust protection for ferrous metals for normal in-plant storage and processing and is also safe on yellow metals.
- Cleans and protects in one step.
- Rejects oil for enhanced washer cleanliness and sump life.
- Does not contain DEA, DEA compounds, DCHA, triazine, phosphates, boron, and silicone.

RECOMMENDED STARTING DILUTIONS:

CIMCLEAN PRODUCTO SP-262T is to be mixed with water for use. Always add concentrate to water. Add no other materials to the concentrate or mix unless approved by your CIMCOOL[®] District Manager.

- Spray Washers: 3% to 5% (0.91 – 1.52 on the refractometer scale)
- Refractometer Factor: 3.3
- 4% Mix pH is typically: 9.1

HANDLING and STORAGE:

If frozen, thaw completely at room temperature. Inside storage is recommended.

SAFETY DATA SHEET:

Available at www.cimcool.com

For additional information refer to its OSHA SDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL[®] Technical Services at 1-888-CIMCOOL.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.