



Product Information Flyer

DESCRIPTION

CIMGUARD 9C is a combination rust preventive, moisture sealant, cleaner and penetrating lubricant in one product.

APPLICATION

CIMGUARD 9C is ideal for both ferrous and non-ferrous metals. It frees frozen corroded parts easily and rapidly by absorption on the metal surface.

FEATURES & BENEFITS

VERSATILE:

CIMGUARD 9C can loosen frozen pipe joints, nuts, bolts, screws and clamps. It will lubricate and stop squeaking hinges, slide mechanisms, precision instruments, and gauges. This product also works well on under the hood and external automotive parts.

CIMGUARD 9C inhibits corrosion on machine surfaces, bushings, tool room parts and any metal area susceptible to corrosion. It also displaces moisture from motors, pumps, switches and wires.

CIMGUARD 9C cleans off light soils from machine beds, chucks, ways, gears and internal machine parts. It is fast drying and requires no mixing or measuring. It can easily be cleaned with either solvent or light duty alkaline cleaners.

RECOMMENDED STARTING DILUTIONS

CIMGUARD 9C is to be used as is. Add no other materials to the concentrate unless approved by your CIMCOOL® District Manager.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Solubility in Water: Insoluble

Boiling Point: >340°F

Flash Point, COC: >124°F

Appearance and Odor: Clear/Chemical

Specific Gravity: .80

VOC Content (by ASTM D2369): 75%

pH Concentrate: NA

HANDLING AND STORAGE

If frozen, thaw completely at room temperature prior to use. Inside storage is recommended.

SAFETY DATA SHEET

Available at www.cimcool.com

For additional information refer to its OSHA MSDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL® Technical Services at 1-513-458-8199.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.