

# CIMPERIAL® 1060CF-HFP



## DESCRIPTION

CIMPERIAL 1060CF-HFP is a chlorine free soluble oil.

## APPLICATION

CIMPERIAL 1060CF-HFP was developed for general machining and grinding applications, such as milling, drilling, turning and grinding operations such as centerless, ID and OD. It is recommended for use in high pressure fluid applications where foam control is critical. It is very well suited for the machining of aluminum but can also be used on ferrous materials. Do not use on magnesium.

## FEATURES & BENEFITS

- Excellent foam control
- Good on most operations; machining and grinding
- Compatible with most materials
- One fluid for all operations
- Chlorine free

## RECOMMENDED STARTING DILUTIONS

CIMPERIAL 1060CF-HFP is to be mixed with water for use. Always add concentrate to water. Add no other materials to the concentrate or mix unless approved by your CIMCOOL® Technical Services Specialist.

- Machining and Grinding 5% - 10% (5.0 to 10.0 on the refractometer scale)
- The Refractometer Factor is 1.0
- 5% mix pH is typically 8.9

## SAFETY DATA SHEET:

Available at [www.cimcool.com](http://www.cimcool.com)

For additional information refer to its OSHA SDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL® Technical Services at 1-888-CIMCOOL.

*Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.*