

# Houghto-Draw 7060

Heavy-duty, bio-stable drawing and stamping fluid for all

## DESCRIPTION

Today's modern stamping and drawing companies require the use of one lubricant capable of working in many applications on a wide variety of metals. **Houghto-Draw 7060** is such a product. Whether you are stamping or forming high and low carbon steel, alloy steels, etc. **Houghto-Draw 7060** is the choice.

**Houghto-Draw 7060** is compatible with hard water and is clean running and bio-stable which assures long, odor-free sump life. It provides corrosion protection without staining.

## FEATURES

- Clean running and bio-stable/ low foam with reduced disposal cost/ less down time/ operator acceptance
- Excellent corrosion protection and in process protection of machinery and parts
- Excellent stamping and forming capabilities with increased tool life and improved surface finish

## RECOMMENDED USE CONCENTRATIONS

Stamping and drawing	5-20%
Pilger Mill Drawing	10-12%

## DATA (TYPICAL VALUES)

Houghto-Draw 7060	
Appearance	Amber color liquid
pH (neat)	10.26
pH (10% in water)	9.69
A.O. Correction factor	1.1
Pounds per gallon, 75°F	7.98

## HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

Date | version  
Code



Houghton International Inc.  
Madison and Van Buren Aves.  
P. O. Box 930  
Valley Forge, PA 19482-0930

Phone: 610-666-4000  
Fax: 610-666-0174  
info@houghtonintl.com  
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.