

Houghto-Draw 7094-L

Special non-chlorinated oil

DESCRIPTION

Houghto-Draw 7094-L is a specially formulated metal forming lubricant offering both economy and great lubricity. This product is also easily removed in alkaline cleaning operations; promoting good phosphate and paint compatibility.

Houghto-Draw 7094-L provides good corrosion protection and can be welded through. Since this product contains no chlorine, there are no surcharges for waste oil removal.

FEATURES

- Light viscosity non-chlorinated lubricant providing excellent lubricity for improved tool and die life
- Low viscosity and low drag-out equals reduced consumption and overall cost savings

DATA (TYPICAL VALUES)

Houghto-Draw 7094-L	
Appearance	Clear amber oil
Viscosity @ 100°F (40°C), SUS	150 + 10
Odor	Bland
Pounds per gallon	7.39
Specific gravity	0.887

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

Date | version
Code



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.