

Houghto-Quench 3440

High Performance, Highly Accelerated Cold Quenching Oil

DESCRIPTION

Houghto-Quench K is an accelerated quenching oil suitable for use at temperatures up to 180°F (82°C). It is based upon specialty solvent refined base oil to minimize oxidation and ensure consistent performance under the most arduous of operating conditions. A carefully formulated additive package is incorporated into Houghto-Quench K to reduce the duration of the vapor blanket cooling stage and provide accelerated quenching characteristics, together with excellent oxidation resistance and thermal stability.

APPLICATION

The highly accelerated speed provided by Houghto-Quench K enables the development of optimum strength and hardness with minimum distortion in lower hardenability and low alloy steels, heavy sectioned components or steels of borderline hardenability.

Houghto-Quench K is suitable for use in all types of quenching installations including open quench tanks, sealed quench furnaces and continuous furnaces of the shaker hearth, cast link and mesh belt type. It is recommended particularly for applications where staining of components during quenching should be minimized.

DATA (TYPICAL VALUES)

ASTM Color	
Viscosity @ 37.8°C (100.0°F)	22.45 cSt = 108.3 SUS
@ 40.0°C (104.0°F)	21.55 cSt = 104.2 SUS
@ 100.0°C (212.0°F)	4.2 cSt = 40.1 SUS
Flash Point	345°F (173.9°C) min.
Fire Point	400°F (204.4°C)
Specific Gravity @ 60°F (15.6°C)	0.871
GM-Quenchometer Speed @ 80°F (26.7°C)	8-10 seconds

Date | version
Code

FEATURES/ BENEFITS

- Fast cooling rate in initial stage of quenching: Maximum metallurgical and physical properties
- Minimal drag-out of quenching oil: Less smoke and makeup required
- Excellent oxidation resistance and thermal stability: elimination for waste due to quench oil degradation

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.