

MILPRO[®] 634



DESCRIPTION

MILPRO 634 is general purpose oil recommended for machining and grinding operations.

APPLICATION

MILPRO 634 can be used on ferrous and most non-ferrous metals. It is recommended for moderate duty applications such as turning, milling, gun drilling and grinding.

LUBRICITY

MILPRO 634 contains a carefully balanced lubrication package comprised of both a physical lubrication component and an extreme pressure additive – contains stable lubricity additives with very low depletion rates and high temperature stability.

RECOMMENDED STARTING DILUTIONS

MILPRO 634 is to be used neat (100%). Add no other materials to the concentrate unless approved by your CIMCOOL[®] District Manager.

- Machining and grinding Neat (100%)

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Solubility in water: Not Soluble
Viscosity (SUS) @ 100°F: 90
pH Concentrate: NA
Total Chlorine, wt.-%: 5.4

Appearance and Odor: Clear/Chemical
Weight, lb./gal, 60°F (15.6 °C): 7.3
Flash Point /Sp.Gr./Boiling Point: SEE SDS
pH Mix 5%, Typical Operating: NA
Total Sulfur, wt.-%: 0

SAFETY DATA SHEET:

Available at www.cimcool.com

For additional information refer to its OSHA SDS on www.cimcool.com website, or contact your local CIMCOOL[®] Technical Service Specialist or you may contact CIMCOOL Technical Services at 1-888-CIMCOOL.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.