

MILPRO[®] 810CF



DESCRIPTION

MILPRO 810CF is a general purpose oil recommended for machining and grinding operations.

APPLICATION

MILPRO 810CF can be used on ferrous and most non-ferrous metals. The MILPRO 810CF is recommended for turning, milling and grinding.

LUBRICITY

MILPRO 810CF contains a carefully balanced lubrication package contains stable lubricity additives with very low depletion rates and high temperature stability.

RECOMMENDED STARTING DILUTIONS

MILPRO 810CF is to be used neat (100%). Add no other materials to the concentrate unless approved by your CIMCOOL[®] District Manager.

Machining and grinding use neat (100%)

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Solubility in water: Insoluble Viscosity (SUS) @ 100°F: 50 pH Concentrate: NA Total Chlorine, wt.%: 0 Appearance and Odor: Clear/Chemical Weight, lb./gal, 60°F (15.6 °C): 7.5 Flash Point /Sp.Gr./Boiling Point: SEE SDS pH Mix 5%, Typical Operating: NA Total Sulfur, wt.%: 0

SAFETY DATA SHEET:

Available at <u>www.cimcool.com</u>

For additional information refer to its OSHA SDS on www.cimcool.com website, or contact your local CIMCOOL® Technical Service Specialist or you may contact CIMCOOL Technical Services at 1-888-CIMCOOL.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.

CIMCOOL FLUID TECHNOLOGY 3000 DISNEY STREET CINCINNATI, OH 45209 2/2018 B00640

