



Product Information Flyer

TYPICAL	MILPRO GEAR 150	MILPRO GEAR 220	MILPRO GEAR 320	MILPRO GEAR 460
Appearance	Clear / Amber	Clear / Amber	Clear / Amber	Clear / Amber
Odor	Bland Oil	Bland Oil	Bland Oil	Bland Oil
Density (3/gal)	7.7	7.7	7.7	7.7
Sp. Gravity	0.92	0.92	0.92	0.92
Viscosity				
cst @ 100°F	150	220	320	460
SUS @ 100°F	700	1025	1480	2100
FLASH POINT (min)	380°F	350°F	370°F	470°F
FREEZE POINT (min)	<30°F	<30°F	<30°F	<30°F

Handling: If frozen, thaw completely and stir before use.

USE AS RECEIVED

Designed to be used in Gear Oil applications where above oils meet required specifications

MILPRO Gear Oils are recommended to be used in accordance with good machine maintenance and hygiene practices and should be changed at regular intervals as required.

Limitation of Liability: *Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.*

CIMCOOL FLUID TECHNOLOGY
10200 ALLIANCE DR.
BLUE ASH, OHIO 45242
1-888-246-2665