

OAK® 50-20 EVAPORATIVE LUBRICANT



Product Information Flyer

DESCRIPTION

OAK 50-20 is an "evaporative" lubricant developed nonferrous bending and expanding in the air conditioning and heat transfer industries.

APPLICATION

OAK 50-20 is primarily used to bend and expand aluminum and copper tubing where post cleaning is prohibitive.

The "evaporative" nature of this unique lubricant supplies high boundary lubrication, while leaving minimal residue.

FEATURES & BENEFITS

LUBRICITY:

Has been pre-tested on fin lines around the world, providing good die and tool life.

CLEANLINESS:

After use, parts may not require post cleaning. Clean running product that does not contain oil.

CORROSION:

Non-staining to aluminum and copper.

ECONOMICAL:

Contains no water to promote rancidity, thereby ensuring optimum shelf-life in lubricant reservoirs. Low end use cost.

RECOMMENDED STARTING DILUTIONS

OAK 50-20 is used as received (100%) and may be applied by spray, dip or brush methods. Add no other materials to the concentrate unless approved by your CIMCOOL representative.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Solubility in water: Insoluble Specific Gravity: 0.80 Flash Point /Sp.Gr./Boiling Point: SEE MSDS pH, Typical Operating 100%: NA Total Sulfur, wt%: 0 Appearance and Odor: Clear/Chemical Weight, lb/gal, 60°F (15.6°C): 6.7 Viscosity SUS @ 100 F: 60 pH Concentrate: NA Total Chlorine/Chlorides, wt%: 0/0 ppm Silicones: None

HANDLING AND STORAGE

If frozen, product separates, Thaw completely at room temperature and stir thoroughly prior to use. Inside storage is recommended.

SAFETY DATA SHEET Available at www.cimcool.com

For additional information refer to its OSHA MSDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL[®] Technical Services at 1-513-458-8199.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.



3000 Disney Street Cincinnati, OH 45209 1-513-458-8199 Fax 1-513-458-8179