

TECHNICAL DATA SHEET

RUST VETO® 210

LIGHT OIL RUST PREVENTIVE

RUST VETO® 210 is an oil-based rust preventive.

Up to 12 month indoor corrosion protection leaving an oily film.

Applications

RUST VETO® 210 can be applied by brush, spray, or dip methods and leaves a light oil film on parts or equipment. Excess material drains rapidly from treated surfaces because of the preventive's light viscosity

Recommendation For Use

Product is used neat.

Benefits

- Excellent humidity rust protection
- Easily removed
- Barium free
- Low-odor nature of the products optimizes worker acceptance.
- The high flash point reduces the potential for flammability.

Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

Typical Physical Properties

PROPERTY	TYPICAL VALUE
Flash Point, °F	350
Kinematic Viscosity @ 100°F (38°C)	24 cSt
Approx. Coverage, sq. ft./gal.	3000
Film thickness	.45 mil
Humidity test	Pass 30+ days

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 20210000

