

# VANISHING COMPOUND 40

## DESCRIPTION

Vanishing Compound 40 is a medium-duty lubricant designed for those applications wherein no oil film is permissible. Vanishing Compound 40 films will evaporate slowly leaving a microscopically thin oil film that possesses excellent lubricity properties.

Parts that require complete removal of residual film must be cleaned using an aqueous or solvent based cleaner.

Vanishing Compound 40 should be used as received and can be applied by spraying, dipping, brushing or roller coating methods.

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT (SCAQMD, RULE 1144):

THIS PRODUCT CANNOT BE USED IN THE SCAQMD

## DATA (TYPICAL VALUES)

Appearance	Clear yellow liquid
Flash Point, TCC	140°F
Evaporation Rate (Butyl Acetate = 1)	0.22

## CAUTION

Product contains solvent.

Use mechanical ventilation and guard against open flames or other ignition sources.

## FEATURES/ BENEFITS

- Odorless carrier solvent evaporates readily leaving a minimum residue so no cleaning is necessary after part is stamped
- Enhanced lubrication package to reduce metal pickup and galling for improved tool and die life

## HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

Date | version  
Code



Houghton International Inc.  
Madison and Van Buren Aves.  
P. O. Box 930  
Valley Forge, PA 19482-0930

Phone: 610-666-4000  
Fax: 610-666-0174  
info@houghtonintl.com  
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.