Vibra-Kleen 534

Rust inhibiting cleaner

DESCRIPTION

Vibra-Kleen 534 is a low temperature, non-nitrited, vibratory cleaner containing in-plant rust inhibition. The low foaming formulation has no chelates, but is stabilized for use in moderately hard water. Vibra-Kleen 534 presents no barrier to subsequent coating or welding. It also works very well in barrel cleaning, and may be used in all stages of multi-stage spray washers.

FEATURES

- Outstanding cleaning capability for optimal soil removal.
- May be used at ambient temperatures to dramatically reduce energy costs.
- Imparts corrosion inhibition to parts to protect them from rusting between operations thereby reducing scrap rates.
- Enhanced metal removal rate reduces cycle times.
- Splits tramp oil which allows for skimming and an extended sump life which reduces chemical costs.
- Incorporates a balance of detergency and surfactancy to provide more effective cleaning.
- Incorporate corrosion inhibitors that prevent flash rusting of your machinery.

DATA (TYPICAL VALUES)

Appearance	Clear, pale yellow liquid
pH (2% Solution)	9.0 <u>+</u> 0.2
Effect on Metals	Safe on all metals
Free Caustic	None
Phosphates	None
Solubility	Freely soluble in water
Operating Temperature	70°F to 140°F
Use Concentration	1 - 10% by volume

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

Date I version Code



Houghton International Inc. Madison and Van Buren Aves. P. O. Box 930 Valley Forge, PA 19482-0930 Phone: 610-666-4000 Fax: 610-666-0174 info@houghtonintl.com www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.