Vibra-Kleen 600

Bio-stable technology

DESCRIPTION

Vibra-Kleen 600 is our pH stable and bio-stable, low temperature, non-nitrited, vibratory cleaner containing inplant rust inhibition. Vibra-Kleen 600 is formulated with ingredients that provide a greater resistance to microbial degradation of the fluid. The low foaming formulation has no chelates, but is stabilized for use in moderately hard water. Vibra-Kleen 600 presents no barrier to subsequent coating or welding. It was designed primarily for the use in Vibratory bowls, but can also be used in some immersion and spray applications. It was especially formulated with advanced aluminum corrosion inhibitors to protect sensitive aluminum alloys from corrosion.

FEATURES

- Outstanding cleaning capability for optimal soil removal.
- May be used at ambient temperatures to dramatically reduce energy costs.
- Bio-stable technology extends sump life and reduces need for costly sump-side biocide addition.
- Enhanced metal removal rate reduces cycle times.
- Incorporates a balance of detergency and surfactancy to provide more effective cleaning.
- Works on a wide variety of alloys which reduces costs via consolidation of products and purchases.
- Formulated to resist biological activity which minimizes use of costly, sump-side biocide addition.

DATA (TYPICAL VALUES)

Appearance	Clear, pale straw liquid
pH (2% Solution)	9.3 <u>+</u> 0.2
Solubility	Freely soluble in water
Operating Temperature	70°F to 140°F
Use Concentration	2 – 5% by volume

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

Date I version Code



Houghton International Inc. Madison and Van Buren Aves. P. O. Box 930 Valley Forge, PA 19482-0930 Phone: 610-666-4000 Fax: 610-666-0174 info@houghtonintl.com www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.