

Cerfa-Kleen 5502

Liquid detergent soak cleaner

DESCRIPTION

Cerfa-Kleen 5502 is a liquid cleaner which has been formulated to provide high surface activity, penetration, and detergency for soak, vibratory and barrel cleaning operations. Cerfa-Kleen 5502 is recommended for the removal of cutting oils, coolants, buffing compounds and general shop dirt. Cerfa-Kleen 5502 will provide up to 14 days indoor rust protection.

Cerfa-Kleen 5502 can be used on ferrous metals, copper, aluminum and zinc. Non-ferrous metals should be processed at lower concentration ranges

FEATURES

- Outstanding cleaning capability for optimal soil removal.
- May be used at ambient temperatures to dramatically reduce energy costs.
- Imparts corrosion inhibition to parts to protect them from rusting between operations thereby reducing scrap rates.
- Incorporate corrosion inhibitors that prevent flash rusting of your machinery.
- Works on a wide variety of alloys which reduces costs via consolidation of products and purchases

DATA (TYPICAL VALUES)

Cerfa-Kleen 5502	
Appearance	Clear yellow liquid
Solubility	Freely soluble in water
pH (2% Solution)	9.2
Rinsability	Free rinsing
Metals	Ferrous metals, copper alloys and aluminum. Aluminum should be processed at lower temperatures
Operating Temperature	Ambient to 140°F
Use Concentration	Vibratory: 1-5% Soak: 3-10%

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

Date | version
Code



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.