

CIMSTAR[®] 700B



DESCRIPTION

CIMSTAR 700B is a semi-synthetic metalworking fluid

APPLICATION

CIMSTAR 700B was developed for use on ferrous and most non-ferrous materials. It can be used on mild steels, stainless steels, hardened steels, ceramics and most aluminum alloys. It should not be used on magnesium alloys.

FEATURES & BENEFITS

- For use in moderate duty machining and grinding applications, such as milling, drilling, turning, and surface grinding.
- Good lubricity – physical and chemical lubricant agents provide good machining and grinding ability.
- The oily residue keeps machine tools and work-piece materials free of corrosion and staining. Good on most non-ferrous alloys as well.
- Has good rancidity control if product concentration is properly controlled.
- Has good foam control.

RECOMMENDED STARTING DILUTIONS:

CIMSTAR 700B is to be mixed with water for use. Always add concentrate to water. Add no other materials to the concentrate or mix unless approved by your CIMCOOL[®] District Manager.

- Machining and Grinding: 5% to 10% (2.4 – 4.8 on the refractometer scale)
- Refractometer Factor: 2.1
- 5% Mix pH is typically 8.9

SAFETY DATA SHEET:

Available at www.cimcool.com

For additional information refer to its OSHA SDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL[®] Technical Services at 1-888-CIMCOOL.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.