

Excelene 516

Heavy Duty Chlorine-Free Cutting and Grinding Oil

DESCRIPTION

Excelene 516 is a straight metalworking oil, designed especially for precision grinding. The product is mainly used with steel, gray cast iron, and non-ferrous heavy metals.

Excelene 516 is particularly suitable for high stock removal rates and grinding speeds due to excellent cooling and detergency properties. The extreme pressure properties ensure improved surface quality, as well as extended tool life.

Hydrocracked base oils prevent Excelene 516 from clouding and ensure minimal evaporation. Air bubbles generated while grinding are released immediately resulting in a continuously even film of lubricant at the grinding site, which promotes reduced loads on tool and work-piece.

Excelene 516 does contain top quality refined products. As a result, polychlorinated compounds (e.g. PCB, PCT, TCDD) do not form, which reduces disposal costs to a minimum.

Excelene 516 is mainly used as a precision grinding oil. However, the product is also suitable for drilling, turning, and milling at high stock removal rates.

DATA (TYPICAL VALUES)

Viscosity @ 100°F	70 - 110 SUS
API Gravity @ 60°F	29 - 32
Flash Point	395°F
Foam Tendency	Low
Chlorine Content	Nil

FEATURES/ BENEFITS

- High lubricity and detergency.
- Chlorine-free.
- Free of heavy metals.
- Low foaming and misting.
- Easily filtered.
- High operator acceptance.
- Enhanced lubricity provides extended tool life and reduces tooling cost.
- Provides improved part finish which reduces overall cost through reduced rework and scrap rates
- Allows grinding wheels to run clean with less loading which saves money by extending time between wheel dressing and wheel changes.

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

Date | version
Code



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.