

Hocut 4800

Heavy duty machining and grinding fluid

DESCRIPTION

Many of today's modern machine shops require the use of one coolant capable of working in many applications on a wide variety of metals. **Hocut 4800** is such a product. It is a versatile product that can be used with many machines including Kingsburys, Bullards, bar machines, lathes, chuckers, centerless and cylindrical grinders. Whether you're cutting high or low carbon steels, alloy steels such as 4130 and 4140; cast iron, nodular iron and gray iron; 300 and 400 series stainless steel, **Hocut 4800** is the choice. It is especially suitable when machining automotive grade aluminum cast alloys including 308, 319, 356, 380, 384 and 390.

Hocut 4800 is compatible with hard water, is clean running and bio-stable, which assures long, odor-free sump life. It provides corrosion protection without staining and affords good lubrication for machine ways and indexing mechanisms. Low foaming characteristics make **Hocut 4800** an excellent choice for gun drilling and other high pressure applications.

RECOMMENDED CONCENTRATIONS

Machining	10:1 to 20:1
Grinding	20:1 to 25:1

CONCENTRATION CHECKS

The refractometer factor for **Hocut 4800** is 1.0. Multiply the refractometer reading by this factor to obtain the emulsion concentration in percent

DATA (TYPICAL VALUES)

Appearance, neat	Amber liquid
Typical in use pH	9.1 – 9.3
Pounds per Gallon, 60°F	8.0008

Date | version
Code

FEATURES/ BENEFITS

- Clean running/low foam for Reduced disposal cost/ less down time/operator acceptance
- Excellent corrosion protection for In-process protection of machinery and parts
- Excellent machining capabilities for Increased tool life; improves surface finish
- Enhanced lubricity provides extended tool life and reduces tooling cost.
- Provides improved part finish which reduces overall cost through reduced rework and scrap rates
- Bio-stable formulation extends sump life indefinitely, reducing waste treatment and recharge costs.
- Allows grinding wheels to run clean with less loading which saves money by extending time between wheel dressing and wheel changes.
- Provides enhanced corrosion inhibition eliminating costly machine tool repair and scrap rate.

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.