

Hocut 801

High Performance, Low Foaming, Semi-Synthetic Coolant for General Purpose Machining and Grinding

DESCRIPTION

Hocut 801 is a versatile, semi-synthetic coolant for machining and grinding of ferrous and nonferrous metals in a wide range of operations. It is formulated with emulsifiers, lubricity additives and inhibitors that offer excellent residual fluid film corrosion protection.

Hocut 801 is compatible with hard water, is clean running and biostable, which assures a long odor-free sump life, and a reduced dependency on any sumpside additives.

FEATURES

- Excellent corrosion protection with in-process protection of machinery and parts
- Clean, odor-free operation and maximizes worker acceptance
- Low foaming tendency and maximizes tool life.

RECOMMENDED USE CONCENTRATION

Machining	5 to 10%
Grinding	5%

DATA (TYPICAL VALUES)

Appearance, Neat	Amber liquid
Appearance, 5% dilution	Hazy Translucent Liquid
Typical in-use pH	9.1-9.3
Pounds per Gallon	8.3

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

Date | version
Code



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.